



Accurately measure UVA, B or C

- Measure damaging UV (ultraviolet) light in the environment and museums.
- UV degradation studies in the pharmaceutical, cosmetic, semiconductor, printing, window tinting, and other industries.
- Laboratory chromatography, electrophoresis and forensics.
- Test UV sterilization and dermatology lamps in hospitals.

UV light intensity appears on the large backlit display in either μW or mW/cm^2 while the small lower display simultaneously shows minimum, maximum, average and recorded data. Up to 20 data points can be recorded automatically at a variety of intervals. Feature zero point reset, hold, and indicates when the battery is low. Comes in a protective, hard, foam-lined carrying case, complete with a UV probe, tripod screw, magnetic mount and a 9V battery. Model 850010 measures short wave UV-C light for applications such as UV light fume hoods, UV sterilization, industrial glass and non-destructive testing. Model 850009 measures long and medium wave UV-A/B for applications such as forensics, chromatography, electrophoresis and dermatology.

DIM: 6" x 2" x 1½" (145 x 55 x 40 mm). WEIGHT: 4.4 oz (135 g).



Model	Wavelength	Calib. point	UV Range	Resolution	Accuracy
850009	280 ~ 400 nm	365 nm	1 $\mu\text{W}/\text{cm}^2$ ~ 40 mW/cm^2	1 μW and 0.01 mW/cm^2	$\pm 4\%$ ± 1 digit (@23 $\pm 5^\circ\text{C}$)
850010	220 ~ 275 nm	254 nm			

No.	Description
850009	UV Light Meter UVA/B
850009C	UV Light Meter UVA/B Certified
850010	UV Light Meter UVC
850010C	UV Light Meter UVC Certified
840090	Water Resistant Instrument Pouch
840092	Benchtop Tripod
840093	Field Tripod